

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

---

1. (currently amended): An image reading device for reading an image while conveying an original on which the image is recorded, comprising:

a plurality of light emitting element units, at each of which a plurality of light emitting elements are arrayed along a first direction which is a direction perpendicular to the original's conveyance direction, said plurality of light emitting element units being linearly disposed along the first direction;

~~a light emission controller which respectively separately controls the light emission of the plurality of light emitting element units in accordance with a size of the original;~~

an optical member for irradiating light emitted from said plurality of light emitting element units across at least a substantially entire width of the original in the first direction; and

photoelectric conversion elements which are disposed in correspondence with said plurality of light emitting element units, receive light that is one of transmitted through and reflected from the image, and conduct photoelectric conversion of the received light,

wherein the image is read while at least one original is conveyed, the original having a width dimension corresponding to a width dimension of one of said plurality of light emitting element units or a combined width dimension of at least two of said plurality of light emitting element units;

wherein at least one light emitting element unit for emitting light is selected among said

**AMENDMENT UNDER 37 C.F.R. § 1.114(c)**  
**U. S. Application No. 09/588,345**

plurality of light emitting element units in accordance with at least one of a first direction  
dimension of the original, a number of originals and a magnification at which the original is to be  
read.

31 2. (original): An image reading device according to claim 1, wherein said optical member is formed by a plurality of light-guiding members which are provided at positions respectively corresponding to positions of said plurality of light emitting element units, and said optical member guides the emitted light to a vicinity of the original and causes the emitted light to be continuous across at least the substantially entire width of the original and to be free of boundary lines.

3. (original): An image reading device according to claim 1, wherein two light emitting element units are provided and the image is read by causing a first direction central portion of one of or both of the light emitting element units to correspond with a first direction central portion of a conveying path of the original, in accordance with a first direction dimension of the original, a number of originals and a magnification at which the original is to be read.

112 4. (currently amended): An image reading device for reading an image while conveying an original on which the image is recorded, comprising:

a plurality of light emitting element units, at each of which a plurality of light emitting elements are arranged along a first direction which is a direction perpendicular to the original's conveyance direction, said plurality of light emitting element units being disposed along the first direction;

~~a light emission controller which respectively separately controls the light emission of the plurality of light emitting element units in accordance with a size of the original;~~

**AMENDMENT UNDER 37 C.F.R. § 1.114(c)**  
**U. S. Application No. 09/588,345**

an optical member for guiding light emitted from each of said plurality of light emitting element units such that the light is irradiated to the original;

an original carrier for positioning the original at a predetermined position and conveying the original; and

a light receiving section for receiving light that is one of transmitted through and reflected from the original;

wherein, in accordance with the original which is set at said original carrier, relative positions, in the first direction, of said light receiving section, the original, said optical member and said plurality of light emitting element units can be altered and light emission of each of said plurality of light emitting element units is respectively separately controlled;

HOW IS THE  
light emitting element  
controlled?

wherein at least one light emitting element unit for emitting light is selected among said plurality of light emitting element units in accordance with at least one of a first direction dimension of the original, a number of originals and a magnification at which the original is to be read.

5. (original): An image reading device according to claim 4, wherein said optical member and said plurality of light emitting element units are movable in the first direction, a position of the original at said original carrier, a position of said optical member, and positions of said plurality of light emitting elements are determined in accordance with at least one of a first direction dimension of the original, a number of originals set concurrently at said original carrier, and a magnification at which reading is to be conducted.

6. (original): An image reading device according to claim 4, wherein said optical member is formed by a plurality of light-guiding members which are provided in respective

**AMENDMENT UNDER 37 C.F.R. § 1.114(c)**  
**U. S. Application No. 09/588,345**

correspondence with said plurality of light emitting element units.

7. (original): An image reading device according to claim 6, wherein each of said plurality of light-guiding members includes a light input section at which light emitted from one of said plurality of light emitting element units enters and a light output section from which the light exits, and end portions in the first direction of the output sections of adjacent light-guiding members contact one another.

8. (currently amended): An image reading device for reading an image while conveying one or more originals on which the image is recorded, comprising:

3.1 a plurality of light emitting element units, at each of which a plurality of light emitting elements are arrayed along a first direction which is a direction perpendicular to the originals' conveyance direction, said plurality of light emitting element units being linearly disposed along the first direction;

~~a light emission controller which respectively selectively controls the light emission of the plurality of light emitting element units in accordance with at least one of a first direction dimension of the conveyed originals and a number of the conveyed originals;~~

an optical member for irradiating light emitted from said plurality of light emitting element units across at least a substantially entire width of the originals in the first direction; and

photoelectric conversion elements which are disposed in correspondence with said plurality of light emitting element units, receive light that is one of transmitted through and reflected from the image, and conduct photoelectric conversion of the received light;

wherein at least one light emitting element unit for emitting light is selected among said plurality of light emitting element units in accordance with at least one of a first direction

*AMENDMENT UNDER 37 C.F.R. § 1.114(c)*  
*U. S. Application No. 09/588,345*

dimension of the originals, a number of the originals and a magnification at which the originals are to be read.

112 9. (original): An image reading device according to claim 8, wherein light emission of said plurality of light emitting element units is respectively selectively controlled in accordance with the number of conveyed originals which are conveyed in parallel.

112 10. (original): An image reading device according to claim 8, wherein light emission of said plurality of light emitting element units is respectively selectively controlled in accordance with the first direction dimension of the conveyed originals

B1 11. (previously presented): An image reading device according to claim 8, wherein said optical member is formed by a plurality of light-guiding members which are provided at positions respectively corresponding to positions of said plurality of light emitting element units, and said optical member guides the emitted light to a vicinity of the originals and causes the emitted light to be continuous across at least the substantially entire width of the originals and to be free of boundary lines.

12. (previously presented): An image reading device according to claim 8, wherein two light emitting element units are provided and the image is read by causing a first direction central portion of one of or both of the light emitting element units to correspond with a first direction central portion of a conveying path of the originals, in accordance with a first direction dimension of the originals, the number of originals and a magnification at which the originals are to be read.

112 13. (original) An image reading device according to claim 8, wherein light emission of said plurality of light emitting element units is respectively selectively controlled in accordance

**AMENDMENT UNDER 37 C.F.R. § 1.114(c)**  
**U. S. Application No. 09/588,345**

with the first direction dimension and the number of originals which are conveyed.

14. (previously presented): An image reading device according to claim 1, wherein said photoelectric conversion elements comprise a three-line charge coupled device (CCD).

15. (previously presented): An image reading device according to claim 1, wherein said optical member comprises an acrylic block having a substantially trapezoid column shape.

16. (currently amended): An image reading device according to claim 1, wherein each of said plurality of light emitting element units comprises ~~[[an]]~~ a LED chip group.

17. (previously presented): An image reading device according to claim 1, wherein an amount of light output from each of said plurality of light emitting element units is separately controlled.

112 18. (previously presented): An image reading device according to claim 1, wherein said light emission is respectively separately controlled in accordance with a size of the original and a density of said image.

19. (previously presented): An image reading device according to claim 4, wherein said photoelectric conversion elements comprise a three-line charge coupled device (CCD).

20. (previously presented): An image reading device according to claim 4, wherein said optical member comprises an acrylic block having a substantially trapezoid column shape.

21. (currently amended): An image reading device according to claim 4, wherein each of said plurality of light emitting element units comprises ~~[[an]]~~ a LED chip group.

112 22. (previously presented): An image reading device according to claim 4, wherein an amount of light output from each of said plurality of light emitting element units is separately controlled.

**AMENDMENT UNDER 37 C.F.R. § 1.114(c)**  
**U. S. Application No. 09/588,345**

112 23. (previously presented): An image reading device according to claim 4, wherein said light emission is respectively separately controlled in accordance with a size of the original and a density of said image.

24. (previously presented): An image reading device according to claim 8, wherein said photoelectric conversion elements comprise a three-line charge coupled device (CCD).

B. 25. (previously presented): An image reading device according to claim 8, wherein said optical member comprises an acrylic block having a substantially trapezoid column shape.

C. 26. (currently amended): An image reading device according to claim 8, wherein each of said plurality of light emitting element units comprises ~~[[an]]~~ a LED chip group.

112 27. (previously presented): An image reading device according to claim 8, wherein an amount of light output from each of said plurality of light emitting element units is separately controlled.

112 28. (previously presented): An image reading device according to claim 8, wherein said light emission is respectively separately controlled in accordance with a size of the originals and density of said image.

---